

REVISION RECORD

REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------

NOTES1:

UL Standard

- 1.Rated voltage/current : 300V / 30A
- 2.Withstanding voltage : AC1600V/1Min.
- 3.Torque value : M3 , 4.43Lb.in
- 4.Wire range : 28~10AWG

IEC Standard

1. Pollution degree	2
Overvoltage category	III
Rate impulse voltage(KV)	4.0KV
Rate voltage(V)	400V
Rate current(A)	32A

- 2.Torque value : M3 , 0.5N·m
- 3.Wire range : 0.2~4mm²


NOTES2:

- 1.Dimension shall be interpreted per ASME Y14.5-2009
- 2.Pitch : 7.62mm, Poles : N=02~12P
- 3.Stripping length : 7mm
- 4.Operating temperature: -40°C~+105°C
- 5.Undimensioned tolerances:





Pitch range in mm		Nominal dimension range in mm						
TO	Over	Over	Over	Over	Over	Over	0.1/10	
6	6 TO 10	10 TO 24	30 TO 30	60 TO 60	100 TO 150	150	<	
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±2'	

6.RoHS Compliance

5EDGK - 7.62 - XXP - 1Y - 00A (H)
 (Series No.) (Pitch) (Poles) (Single Pitch) (Color):1.(Grey)
 2.(Blue)
 3.(Black)
 4.(Green)
 5.(Orange)
 6.(Red)
 7.(Transparent)
 8.(Yellow)
 9.(White)



2P



DETACHED LISTS	PART NO.:	/			
	APPD:	/			
	CHKD:	/			
	DRFT:	/			
	DRAWING NO.:		/		SHEET
THIRD ANGLE PROJECTION		DO NOT SCALE DRAWING		SCALE	1:1

NINGBO DEGSON ELECTRICAL CO., LTD

5EDGK-7.62-XXP-1Y-00A(H)

CUSTOMER DRAWING

DRAWING NO.:

MM (INCH)

REV

SHEET

SCALE

DO

1/1

1:1