



Asset | Logistics Tag

ABS DISCTAGS

APPLICATIONS

- Production
- Warehouse
- Logistics

FEATURES

- Black ABS Material
- HF or LF Frequency
- ø 22, 30 or 50 mm
- Opaque Surface
- IP66 Protection

RFID OPTIONS

- HF (ISO 14443 A | ISO 15693)
- LF (EMxxx | Atmel | NXP)

PRODUCT DESCRIPTION

The ABS DiscTags from iDTRONIC Professional RFID are well suited for the identification of goods and objects in an industrial environment. Typical application areas are in logistics, warehouses or productions. The round shape and the ultra-thin thickness fits for reusable transport containers or industrial goods such as in container tracking.

The housing is made of Acrylnitril-Butadien-Styrol and is coloured black with a opaque surface. It is available in three different dimensions: ø 22, 30 or 50 mm. The 30 mm and 50 mm version can delivered with a centre hole on request.

Thanks to the IP66 protection class it features special resistance in rough applications and are stable against many different chemicals. Their water absorbing is low (depending on temperature). It withstands temperature environments of -40 °C up to +75 °C.

The ABS DiscTags are available in the two different RFID frequencies: HF (13.56 MHz) and LF (125 kHz).

TECHNICAL DATA

PRODUCT SPECIFICATIONS

Material	ABS (Acrylnitril-Butadien-Styrol)
Colour	Black
Diameters	∅ 22 × 2.4 mm (no centre hole) ∅ 30 × 2.1 mm (3 mm centre hole) ∅ 50 × 2.1 mm (5 mm centre hole)
Surface	Opaque
Protection Class	IP 66
Application Temperature	-40 °C to +75 °C

AVAILABLE LF: 125 KHZ ICS

IC TYPE	MEMORY	MODE
EM 4100/4200	8 Byte	Read-only
EM 4450/4550	125 Byte	R/W
Atmel Temic 5567	28 Byte	R/W
NXP Hitag 1	256 Byte	R/W
NXP Hitag 2	32 Byte	R/W

AVAILABLE HF: 13.56 MHZ ICS

IC TYPE	MEMORY	MODE
NXP MIFARE Ultralight®	512 bit	ISO 14443 A
NXP MIFARE® Classic 1K EV1	1024 Byte	ISO 14443 A (1-3)
LEGIC MIM256 LEGIC MIM1024	256 Byte 1024 Byte	ISO 14443 A
NXP I-Code SLI NXP I-Code SLI-S	128 Byte 256 Byte	ISO 15693

OTHER ICS ARE AVAILABLE ON REQUEST!

iDTRONIC GmbH
Donnersbergweg 1
67059 Ludwigshafen
GERMANY

Phone +49 (0) 621 66 90 09 4-0
Fax +49 (0) 621 66 90 09 4-9
E-Mail: info@idtronic-rfid.com
Web: idtronic-rfid.com

For further information & prices, please contact info@idtronic.de

Subject to alteration without prior notice
©2019 iDTRONIC GmbH